





HIPPOWRAP™

 $\mathsf{HIPPOWRAP}^\mathsf{TM}$ is the next generation of engineered woven extrusion coated fabric that provides protection for all your valuable investments. $\mathsf{HIPPOWRAP}^\mathsf{TM}$ is very strong yet light weight, exible and tougher than any other plastic Im of same thickness and weight.

KEY APPLICATIONS

HIPPOWRAP™ comes as an brilliant solution for all your indoor and outdoor applications such as fumigation covers, agriculture tarps, for drying of chillies, spices, areca nuts, turmeric, grapes (raisin) and other agricultural produce, poultry curtain and roofs, temporary shelters, Raw Bricks covers, truck tarps, wagon covers, machine covers, industrial packaging and much more.

KEY FEATURES

- $\mathsf{HIPPOWRAP}^\mathsf{TM}$ complies with Bureau of Indian Standard code IS 7903: 2017. Exceptionally resilient, the highest strength to weight ratio of any plastic Im.
- Its all weatherproof, with the ability to withstand tough climate extremes.
- Technically designed UV stabilized fabric, withstand long term exposure to the sun and resist radiation.
- Unaffected by most cleaning chemicals and surfactants, inert to bacteria and mould growth.

 It offers the assurance of 100% waterproo ng because of its specialty polymer multilayered extrusion coating.
- High tensile and tear strength ratings.
- Resilient Impact and Puncture resistant, product hold its shape while remaining exible up to 22% stretch.
- Lightweight, Flexible and easy to handle, transport and Use.
- Available in varied GSM: 80, 100, 125, 150, 180, 200, 230.
- Above all, its 100% Recyclable, an Eco Friendly Im.

STANDARD SIZES

Available in any width and length, duly hot sealed, subject to MOQ. It can be supplied in customized sizes, thickness and colors, subject to MOQ.

STANDARD COLOUR

Standard available colours are Blue/Blue, Yellow/Yellow, Olive Green/Olive Green, Black/Black & Natural Colour.

CHEMCO PLASTIC INDUSTRIES PVT. LTD.



HEAD OFFICE

Chemco House, 6th Floor, D Sukhadwala Road, Fort, 78 Virwani Industrial Estate, off W. E. Highway, 1rvine, California 92620 Mumbai 400001, India, Telephone: +91 22 22821777 : Goregaon East, Mumbai 400063, Mobile: +91 99744 04255

EXPORT OFFICE

UNITED STATES OFFICE

Mobile: +1 (949) 394-7566









HIPPOPROTEC™ FILM & LINERS

HIPPO PROTEC[™] Film & Liners are premium three-layer extrusion blown Ims manufactured with Reifenhauser technology which is known for world class blown Im technology. This technology enables us to process raw materials that guarantee the highest level of mechanical strength and exibility, and compatibility with all mechanical testing standards.

The Reifenhauser technology is known for:
The extra ordinary strength orientation in transverse direction.
Outstanding tearing properties in the Im.
Outstanding tensile strength in both MD & TD.

Outstanding impact strength for heavy duty application.

Over all thickness variation control thought the OBC & IBC systems.

Excellent colour dispersion.



HIPPO PROTEC[™] fabric ranges from 25 microns to 400 microns without gauge variation Customer Custom Im available in all colours subject to MOQ.

Roll length is as per customer requirement.

Up to 150 inch lay at width from 25 microns to 400 microns.

KEY APPLICATIONS

- Greenhouse Ims Tunnel Ims
- · Mulching Ims
- · Silage cover Ims
- Silage tubes

Silage stretch Ims

· Dunnage Sheets

TECHNICAL SPECIFICATION

| SR. NO. | FILM PROPERTIES | | TEST METHOD | UOM | 225 GSM VALUE | 140 GSM VALUE | 60 GSM VALUE |
|------------|--------------------------|----|-------------|-----------------|------------------|------------------|-----------------|
| 1 | Average Pro le Thickness | | ASTM F 2251 | μ | 240 | 150 | 65 |
| 2 | 2 Sigma Range | | ASTM D 6988 | | 3.8 | 4.2 | 3.9 |
| 3 | Mass (g/m²) | | ASTM D 4321 | GSM | 225 | 140 | 60 |
| 4 | Film Width | | ASTM F 2203 | Inch | 150 | 150 | 150 |
| 5 | Tensile Stress @ Yield | MD | ASTM D 882 | Mpa or N/mm² | 22 | 20 | 19 |
| | | TD | | | 19.5 | 17 | 16.5 |
| 6 | Elongation @ Break | MD | ASTM D 882 | % | 690 | 615 | 645 |
| | | TD | | | 815 | 715 | 710 |
| 7 | Static Charge | | ASTM D 4470 | kv | 5.2 | 5.3 | 5.1 |

CHEMCO PLASTIC INDUSTRIES PVT. LTD.



HEAD OFFICE

Chemco House, 6th Floor, D Sukhadwala Road, Fort, 78 Virwani Industrial Estate, off W. E. Highway, 1rvine, California 92620 Mumbai 400001, India, Telephone: +91 22 22821777 : Goregaon East, Mumbai 400063, Mobile: +91 99744 04255

EXPORT OFFICE

UNITED STATES OFFICE

Mobile: +1 (949) 394-7566

